

Technical overview process and conveyor belts

Lagerførte transportbånd



Article code	Article name	Belt thickness (mm)	Hardness topside (Shore)	Weight (kg/m)	Force at 1% elongation (N/mm)	Temperature min. (°C)	Temperature max. (°C)	Temperature min. short (°C)	Temperature max. short (°C)	Min. pulley diameter flexing (mm)	Min. pulley diameter back flexing (mm)	Width standard (mm)	Width max. (mm)
513039	Elastoflex EM 8/2 00+P38 light green AS	2.10	55A	2.40	8.0	-15	80	-15	100	25.0	50.0	1500	1500
577600	Felt EM 10/2 FE+FE black AS	5.00	.	4.50	10.0	-15	80	-15	100	80.0	80.0	1940	1940
570660	Fabric EF/C 6/2 00+0 (PU) white FG	1.50	.	1.40	6.0	-30	90	-30	110	8.00	20.0	2100	2100
576070	Fabric EF/C 8/2 0+0 white FG	1.60	.	1.70	8.0	-10	90	-10	110	15.0	20.0	2000	2000
576760	Fabric EF/C 10/3 0+0 white FG	2.50	.	2.80	10.0	-15	80	-15	100	60.0	80.0	2000	2000
576680	Flexam EF 5/1 0+07 black	1.20	80A	1.00	5.0	-15	80	-15	100	30.0	30.0	2020	2675
576162	Flexam EF 10/2 A18+A42 grey	5.20	35A	4.40	10.0	-15	80	-15	100	80.0	140.0	2000	2000
573650	Flexam EF 10/2 A18+07 green FG	3.00	80A	3.20	10.0	-15	80	-15	100	50.0	80.0	2000	3000
573310	Flexam EM 8/1 A18+06 green FG	2.30	80A	2.40	8.0	-15	80	-15	100	25.0	35.0	2000	2000
575760	Flexam EM 8/2 0+04 green AS FG	1.90	80A	2.10	8.0	-15	80	-20	100	25.0	50.0	2000	3000
572302	Flexam EM 8/2 0+A34 dark green	4.40	35A	3.50	8.0	-25	80	-25	100	40.0	50.0	2000	2000
575330	Flexam EM 10/2 0+07 green FG	2.30	80A	2.50	10.0	-15	80	-15	100	40.0	80.0	2000	3000
576320	Flexam EM 10/2 0+07 grey	2.50	80A	2.70	10.0	-15	80	-15	100	40.0	80.0	2000	2850
575222	Flexam EM 10/2 0+A42 grey	4.70	35A	3.80	10.0	-15	80	-15	100	60.0	140.0	2000	2000
577702	Flexam EX 10/2 0+A8 grey AS	2.90	35A	3.30	10.0	-15	80	-15	100	50.0	80.0	2000	3000
578491	Flexam EX 10/2 0+05 black M2 AS / 2.1 mm	2.10	80A	2.60	10.0	-15	80	-15	100	30.0	60.0	2000	2000
574122	Flexam EX 10/2 0+A32 black AS	2.70	35A	2.20	10.0	-25	80	-25	100	25.0	40.0	2000	3000
574451	Flexam ES/M 6/2 0+04 black M2	1.80	88A	2.40	6.0	-15	80	-15	100	30.0	50.0	2000	2000
575080	Nonex EF 10/2 A18+07 white FG / 3.2 mm	3.20	65A	3.40	10.0	-15	80	-15	100	50.0	80.0	2000	3000
574152	Nonex EF 10/2 A18+A13 white FG	6.00	65A	5.10	10.0	-15	80	-15	100	80.0	140.0	1900	2000
570090	Nonex EM 5/1 0+02 white FG	0.80	65A	0.90	5.0	-15	80	-15	100	6.00	30.0	2000	3000
571260	Nonex EM 8/1 A18+06 white FG	2.30	65A	2.40	8.0	-15	80	-15	100	25.0	35.0	2000	2000
529108	Nonex EM 8/2 00+05 white FG	2.00	65A	2.20	8.0	-15	80	-15	100	25.0	50.0	2000	3000
575700	Nonex EM 8/2 00+05 light blue FG	2.00	65A	2.30	8.0	-15	80	-15	100	25.0	50.0	2000	3000
575232	Nonex EM 8/2 00+A15 white FG	2.70	65A	2.30	8.0	-15	80	-15	100	25.0	50.0	2000	2000
575233	Nonex EM 8/2 00+A18 white FG / 2.6 mm	2.60	65A	2.60	8.0	-15	80	-15	100	25.0	50.0	2000	2000
572490	Nonex EM 8/2 07+07 white FG	3.10	65A	3.70	8.0	-15	80	-15	100	80.0	80.0	2000	3000
573330	Nonex EM 10/2 00+07 white FG / 2.5 mm	2.50	65A	2.80	10.0	-15	80	-15	100	40.0	80.0	2000	2000
576000	Nonex EF 10/2 A18+07 light blue FG	3.20	65A	3.40	10.0	-15	80	-15	100	50.0	80.0	2000	3000
575730	Nonex EM 10/2 00+09 light blue FG	2.60	65A	2.80	10.0	-15	80	-15	100	40.0	80.0	2000	3000
579921	Poliflex EF/M 8/2 00+03 (PU) transparent M2 AS FG	1.70	36D	1.60	8.0	-20	60	-20	80	14.0	70.0	2000	2000
590498	Ropanol EM 4/1 00+00 light green FG	0.50	.	0.40	4.0	-20	80	-25	100	3.00	3.00	2000	2000
578180	Ropanol EM 6/2 00+00 (PU) transparent AS FG	1.40	.	1.30	6.0	-20	60	-20	80	6.00	15.0	2000	2000
579550	Ropanax EX 10/2 0+02 (PU) black AS	1.60	60D	1.70	10.0	-20	90	-20	110	50.0	100.0	2000	2000
579640	Ropanyl DM 8/2 04+04 white AS FG	1.95	93A	2.20	8.0	-20	90	-30	110	30.0	30.0	2000	2000

Technical overview process and conveyor belts

Lagerførte transportbånd



Article code	Article name	Belt thickness (mm)	Hardness topside (Shore)	Weight (kg/m)	Force at 1% elongation (N/mm)	Temperature min. (°C)	Temperature max. (°C)	Temperature min. short (°C)	Temperature max. short (°C)	Min. pulley diameter flexing (mm)	Min. pulley diameter back flexing (mm)	Width standard (mm)	Width max. (mm)
579900	Ropanyl DM 8/2 04+04 light blue AS FG	2.00	93A	2.20	8.0	-20	90	-30	110	30.0	30.0	2000	2000
525005	Ropanyl EM 4/1 00+02 white FG	0.70	93A	0.80	4.0	-20	90	-30	110	8.00	10.0	2000	3000
574001	Ropanyl EM 4/1 0+02 light blue M2 FG	0.65	93A	0.70	4.0	-20	90	-30	110	8.00	10.0	2000	2000
599080	Ropanyl EM 6/1 00+02 white AS FG	0.65	85A	0.70	6.0	-20	90	-30	110	5.00	12.0	1500	2000
577951	Ropanyl EM 6/2 00+02 white M2 AS FG	1.50	85A	1.65	6.0	-20	90	-30	110	6.00	40.0	2000	2000
577990	Ropanyl EM 6/2 00+02 light blue AS FG	1.50	85A	1.65	6.0	-20	90	-30	110	6.00	40.0	2000	2000
577952	Ropanyl EM 6/2 00+A21 white AS FG	1.65	85A	1.65	6.0	-20	90	-30	110	6.00	40.0	2000	2000
577200	Ropanyl EM 8/2 00+02 white AS FG	1.60	93A	1.70	8.0	-20	90	-30	110	14.0	50.0	2000	2000
577391	Ropanyl EM 8/2 00+02 dark green M2 AS FG	1.60	93A	1.70	8.0	-20	90	-30	110	14.0	50.0	2000	2000
577001	Ropanyl EM 8/2 00+02 light blue M2 AS FG	1.60	93A	1.70	8.0	-20	90	-30	110	14.0	50.0	2000	2000
511444	Ropanyl EM 10/2 00+10 transparent M2 FG	2.50	85A	2.90	10.0	-20	90	-30	110	80.0	120.0	1500	1900
593900	Ropanyl ESM 10/2 00+02 white FG NF	1.30	93A	1.40	10.0	-20	90	-30	110	8.00	25.0	2000	2000
571440	Silam EM 6/2 00+02 (PU) white AS FG	1.45	30A	1.50	6.0	-20	90	-30	110	6.00	40.0	2000	2000