

CONTI® SYNCHROCOLOR

Silicone-free timing belt - free of substances that damage paintwork

Properties:

- temperature range, depending on application, from -20°C to +100°C
- paint compatible
- free of silicon
- electrically conductive to ISO 9563
- conditionally resistant to oil
- ozone-resistant
- suitable for tropical climates
- o aging-resistant
- suited for counterbending/back-tensioners
- maintenance free





Heavy-duty CONTI® SYNCHROCOLOR CXP and CONTI® SYNCHROCOLOR CXA types are available on request.

HTD

Profile	Length range L_p (mm)
HTD 8M Color	480 - 2800
HTD 14M Color	966 - 3500

HTD CXP

Profile	Length range L_p (mm)
HTD 8M Color CXP	480 - 2800
HTD 14M Color CXP	966 - 3150

HTD CXA

Profile	Length range L_p (mm)
HTD 8M Color CXA	480 - 3408
HTD 14M Color CXA	1190 - 4578

The content of this publication is not legally binding and is provided as information only. The trademarks displayed in this publication are the property of Continental AG and/or its affiliates. Copyright © 2015 ContiTech AG. All rights reserved. For complete information go to: www.contitech.de/discl_en

Power Transmission Group ContiTech Antriebssysteme GmbH D-30169 Hannover · Phone +49 511 938 - 71 industrie.as@ptg.contitech.de

